


PRODUCT DATA SHEET

AUTOMATIC WATER CONDITIONING SYSTEMS

HIGH FLOW COMMERCIAL 2900 SERIES SYSTEMS



Hub & Lateral Distributor System For Even Flow

Standard Features:

- Electronic Control
- 2" Female Inlet/Outlet Connections
- Fleck 2900 Lead Free Brass Valve
- Motor-Driven Piston-Operated
- Premium Grade Softening Media
- Hard Water By-Pass
- Fiberglass Resin Tank
- Seamless Brine Tank
- Safety Overflow System
- Dry Salt-Grid System (Through 30" Brine Systems)
- Ports for Pressure Gauges & Sample Valves

Optional Features:

- Mechanical Control
- Mechanical Meter
- Steel & Customized Resin Tanks
- ASME Certified Tanks
- Pressure Gauges
- Sample Valves

Choice of Brine Tanks (Shown Below)

Type	Dimensions	Salt Cap.	Salt Grid
Blow Molded	24" x 50"	800 lb	Yes
Rotational Molded	30" x 48"	1200 lbs	Yes
Rotational Molded	39" x 48"	2500 lbs	No
Rotational Molded	42" x 60"	3600 lbs	No

PRODUCT SPECIFICATIONS

Model No.	Media Qty Cubic Feet	Grains of Capacity			Flow @ 15 psi drop	Flow @ 25 psi Drop	Media Tank Dia. x H	Max Drain Flow gpm	Distributor Type
		15 lbs/cu. ft.	10 lb /cu. ft.	5 lbs /cu.ft.					
300	3.0	90000	75000	60000	32 gpm	50 gpm	14" x 65"	4.0	Std
400	4.0	120000	100000	80000	42 gpm	55 gpm	16" x 65"	5.0	Std
500	5.0	150000	125000	100000	50 gpm	65 gpm	18" x 65"	7.0	Std
700	7.0	210000	175000	140000	60 gpm	85 gpm	22" x 60"	10.0	Hub & Lat
1000	10.0	300000	250000	200000	72 gpm	95 gpm	24" x 72"	12.0	Hub & Lat
1500	15.0	450000	375000	300000	80 gpm	110 gpm	30" x 72"	20.0	Hub & Lat
2000*	20.0	600000	500000	400000	94 gpm	125 gpm	36" x 72"	30.0	Hub & Lat

Exchange capacity based on treating water with 10 grains per gallon total hardness @ 10 gpm per cu ft and free of color, odor, and turbidity.

* Minimum salt dosage is 6 lbs. per cu. ft.

ADDITIONAL OPERATING INFORMATION

Not intended to be used to treat water that is Micro biologically unsafe or of unknown quality.
Installation must comply with all state and local codes.
Tank dimensions are based on fiberglass only. Steel tank dimensions may vary.

Operating Water Temperature Range
Operating Ambient Temperature Range
Operating Pressure Range
UL approved electrical components

Max 100°
Max 120°
Max 125 psi

Minimum 35°
Minimum 35°
Minimum 20 psi

110v - 60 hz

